




KNAUFCEILING
Solutions

DATASHEET
ARMSTRONG
ANF RH95



Armstrong ANF RH95 offers a non-directional pin hole visual and Excellent Light Reflectance.

- Non-directional pin hole visual saves installation time & wastage
- Superior humidity resistance: RH99

APPLICATION AREAS

- Office
- Education
- Healthcare
- Retail

KNAUFCEILINGSOLUTIONS.COM

YOUR **CEILING**
OUR **SOLUTIONS**

DATASHEET
ARMSTRONG ANF RH95

Edge details		Board 	Tegular 24 	Tegular 15 BE 														
Thickness (mm)		15	15	15														
Dimensions (mm)		600 x 600	600 x 600	600 x 600														
System		Exposed Grid System, Demountable Ceiling (Prelude 24 mm)		Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)														
Weight		≅ 3.0 kg/m²																
Colour		White																
Sound absorption		<p>NRC = 0.50</p> <table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_p</td> <td>0.31</td> <td>0.33</td> <td>0.57</td> <td>0.70</td> <td>0.46</td> <td>0.35</td> </tr> </tbody> </table>			Frequency f (Hz)	125	250	500	1000	2000	4000	α_p	0.31	0.33	0.57	0.70	0.46	0.35
Frequency f (Hz)	125	250	500	1000	2000	4000												
α_p	0.31	0.33	0.57	0.70	0.46	0.35												
Sound attenuation		CAC = 30 dB																
Fire reaction		Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84																
Light reflectance		Up to 85%																
Thermal conductivity		$\lambda =$ 0.052 - 0.057 W/mK																
Humidity resistance		Up to 95% RH																
Recycled content		Up to 30%																
Cleanability		Wipeable with dry cloth																
		Wipeable with damp cloth																
Sustainability	 																	

Products may vary from country to country. Please contact your local sales representative.
For further information and legal notice, please visit our website.