




KNAUFCEILING
Solutions

DATASHEET
ARMSTRONG
FINE FISSURED[®] RH99



Armstrong FINE FISSURED RH99 offers a non-directional fissured visual.




















- Non-directional fine fissured visual
- Available in files & planks options
- Good sound absorption: 0.60 NRC
- Superior humidity resistance: RH99

APPLICATION AREAS

- Office
- Education
- Healthcare
- Retail
- Corridors & Lobbies

[KNAUFCEILING.COM](https://www.knaufceiling.com)

YOUR **CEILING**
OUR **SOLUTIONS**

Edge details 	Board 	Tegular 24 	Tegular 15 BE 														
Thickness (mm) 	16																
Dimensions (mm) 	600 x 600 600 x 1200	600 x 600 600 x 1200	600 x 600 600 x 1200														
System 	Exposed Grid System, Demountable Ceiling (Prelude 24 mm)		Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)														
Weight 	$\approx 3.2 \text{ kg/m}^2$																
Colour 	White																
Sound absorption 	NRC = 0.60 <table border="1" data-bbox="539 949 1265 1037"> <thead> <tr> <th>Frequency <i>f</i> (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_p</td> <td>0.39</td> <td>0.34</td> <td>0.48</td> <td>0.74</td> <td>0.84</td> <td>0.74</td> </tr> </tbody> </table>			Frequency <i>f</i> (Hz)	125	250	500	1000	2000	4000	α_p	0.39	0.34	0.48	0.74	0.84	0.74
Frequency <i>f</i> (Hz)	125	250	500	1000	2000	4000											
α_p	0.39	0.34	0.48	0.74	0.84	0.74											
Sound attenuation 	CAC = 35 dB																
Fire reaction 	Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84																
Light reflectance 	Up to 85%																
Thermal conductivity 	$\lambda = 0.052 - 0.057 \text{ W/mK}$																
Humidity resistance 	Up to 99% RH																
Recycled content 	Up to 32%																
Cleanability 	Wipeable with dry cloth Wipeable with damp cloth																
Sustainability	 																

Products may vary from country to country. Please contact your local sales representative.
For further information and legal notice, please visit our website.